

United States Patent [19]

Nakashiba et al.

[11] Patent Number: **5,762,539**[45] Date of Patent: **Jun. 9, 1998**[54] **APPARATUS FOR AND METHOD FOR
POLISHING WORKPIECE**401216768 8/1989 Japan 451/288
404217456 8/1992 Japan 451/288
6-333891 12/1994 Japan .[75] Inventors: **Masamichi Nakashiba, Mitaka; Norio
Kimura, Fujisawa; Isamu Watanabe;
Kaori Yoshida, both of Tokyo, all of
Japan**[73] Assignee: **Ebara Corporation, Tokyo, Japan**[21] Appl. No.: **887,463**[22] Filed: **Feb. 27, 1997**[51] Int. Cl.⁶ **B24B 5/00**[52] U.S. Cl. **451/41; 451/5; 451/285;
451/286; 451/287; 451/288; 451/289; 451/388**[58] Field of Search **451/41, 285-289,
451/388, 53, 5**[56] **References Cited****U.S. PATENT DOCUMENTS**4,373,991 2/1983 Banks .
5,584,751 12/1996 Kobayashi et al. 451/41
5,605,488 2/1997 Ohashi et al. 451/41
5,670,011 9/1997 Togawa et al. 451/41**FOREIGN PATENT DOCUMENTS**

401109066 4/1989 Japan 451/288

OTHER PUBLICATIONSU.S. Pat. application Ser. No. 08/524,824, filed Sep. 7, 1995,
Kimura et al., entitled "Method and Apparatus for Polishing
Workpiece".

Primary Examiner—Robert A. Rose

Assistant Examiner—George Nguyen

Attorney, Agent, or Firm—Wenderoth, Lind & Ponack

[57] **ABSTRACT**

A polishing apparatus for polishing a workpiece such as a semiconductor wafer has a turntable with a polishing surface, and a top ring for holding a workpiece and pressing the workpiece against the polishing surface under a first pressing. The polishing apparatus has a pressurized fluid source for supplying pressurized fluid, and a plurality of openings provided in the holding surface of the top ring for ejecting the pressurized fluid supplied from the pressurized fluid source. A plurality of areas each having the openings are defined on the holding surface so that the pressurized fluid is selectively ejectable from the openings in the respective areas.

ea

11 Claims, 9 Drawing Sheets